

NAČIN POVEZAVE NAPRAV

reduxi

Take Control. Use Reduxi.

Tip kabla:


- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2



Omrežje

Tip kabla:

- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2
- TCP Modbus: cable UTP CAT6A



Sončna elektrarna

Tip kabla:


- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2
- TCP Modbus: cable UTP CAT6A



Drugo

Tip kabla:

- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2
- TCP Modbus: cable UTP CAT6A



Hranilnik energije



Reduxi:

- Napajalna napetost: 12 - 24 V DC
- Žična ali brezžična povezava do interneta
- 2 x RS485 port

Tip kabla:

- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2
- TCP Modbus: cable UTP CAT6A



Polnilna postaja

Tip kabla:

- RS485 Modbus: cable BUS LD FD 2x2x0 22 mm2
- RS485 Modbus: cable twisted pair J-Y(St)Y 2X2X0,8 mm2
- TCP Modbus: cable UTP CAT6A



HVAC

@ www.reduxi.eu

youtube
/@reduxi

f /reduxi

in /company/reduxi-energy-management-system